

## DISC HARROW

**MOUNTED OFFSET DISC HARROW** 



## SALIENT FEATURES

Premium Grade Raw Material • Heavy Duty disc to absorb sudden impact

Sealed Bearing increase life & Reduce maintenance • Heavy duty reinforced pipe frame

Robust bearing hub mechanism & bearings • Superior powder coated paint

## MAIN FEATURES

Suitable for light & medium soil.
High quality boron steel disc.
Tillage depth of harrow 127-178 mm
Used for chop-up unwanted weeds or crop residues.
Useful for open field for superficial ploughing for shattering of clods.
Preparing seed bed, burial of organic substance & remains of cut of crop.
Sealed bearings increase life & reduce maintenance
Maintenance free performance & Longer Life.
Used for breaking soil clods into smaller pieces.
It can be easily mounted & attached with any tractor model.
Better pulverization.



## **TECHINCAL SPECIFICATION**

DESCRIPTION	6x6	7x7	8x8	9x9	10x10	11x11	12x12
FRAME (mm)	75 X 10 Angle Frame With 100 x 50 Front Channel						
GANG BOLT / AXLE (mm)	31.5 (Solid Sq. Rod)						
NO. OF DISC	12	14	16	18	20	22	24
TYPE OF DISC	Notched Disc in Front Gang & Plain Disc In Rear Gang						
DISC DIAMETER (mm)	560						
DISTANCE BETWEEN DISCS(mm)	228						
BEARING HUBS	4		6	8			
MOUNTED CAT.	Standard or Cat-II(optional)						
WIDTH OF CUT(mm Approx.)	1370-1420	1585-1635	1798-1852	2018-2068	2235-2285	2450-2500	2668-2718
WEIGHT	390	430	500	575	615	675	730
TRACTOR POWER (HP)	30-35	40-45	50-55	60-65	70-75	80-90	90-100



Heavy duty SGRN bearing hub



Gang axle Lock



Adjustment Rod



Boron steel disc with good combination of notched disc.



H.O: Plot No. 29 and 31, Aggarwal Mall, CBD Ground, Near Karkardooma Court, Delhi-110032 (India)
Phone: +91 11 22600700, Fax: +91 11 22377472

Works: Jalandhar Road, Hoshiarpur-146022, Punjab (India) Phone: +91 1882 302220, 302221, Fax: +91 1882 302293 e-mail: exports@sonalika.com, url: www.sonalika.com

Auth. Dealer